



ŚNIEŻKA MULTISPRAY GENERAL PURPOSE SPRAY PAINT (ANTIQUÉ GOLD)

- long-lasting and vivid colours.
- resistance to weather and mechanical conditions.
- for interior and exterior use

PRODUCT DESCRIPTION

Śnieżka Multispray GENERAL PURPOSE SPRAY PAINT is a product manufactured on the basis of modified and synthetic resins, featuring ideal coverage, high gloss and guaranteed colour repeatability. Can be used for most available substrates excluding certain plastics and polyurethane.

USE (PURPOSE)

General purpose application - decoration and protection of surfaces made of wood, metal, stone and concrete.

PRODUCT PROPERTIES

Coat drying time at temp. $20\pm 2^{\circ}\text{C}$ and relative humidity over $55\pm 5\%$
degree 1, maximum : [min.] 30
Coat drying time at temp. $20\pm 2^{\circ}\text{C}$ and relative humidity over $55\pm 5\%$
degree 3, maximum : [h] 2
Full coat setting : [h] 24
Coat look : gloss, matt

APPLICATION

Substrate preparation

- The substrate must be dry, dust and rust free as well as free from any grease and other contamination.
- New surfaces must be primed by MULTISPRAY Undercoat.
- Old coats of oil-based paints, with poor adhesive properties to the substrate, rust, dirt and other contamination must be removed, if necessary, the bare substrate must be primed.
- Old, good quality coats must be abraded by a fine-grained sandpaper and dusted off.

Product preparation

- Before use shake the container vigorously. Shake for at least 2 minutes till hearing a characteristic sound of balls moving in the container.

Painting

- Ideal application temperature: from $+15^{\circ}\text{C}$ to $+25^{\circ}\text{C}$.
- It's recommended to apply a few thin coats (2-3) from the distance of 25-30 cm.
- Apply next coat within 2 hours or after 24.

BEST BEFORE DATE

10 years from the date of manufacture

CONTAINERS

400ml

EFFICIENCY

approx. 0,8 - 1.2m² per one container

COLOURS

17 colours + colourless

STANDARDS, TESTS AND CERTIFICATES

ZN-SN-044:2011

FIRE AND HSE RECOMMENDATIONS



UN1950

ATTENTION!

The information included in the technical data sheet is to provide an efficient use of the product, however, it cannot form grounds for the manufacturer's liability, since the performance conditions are beyond its control. It's forbidden to make any adjustments to the product's formula, which can significantly decrease the properties of the used material. In the event of combining the product with other products, the manufacturer shall not bear any responsibility. All the information above is given in good faith, based on current knowledge and experience. The manufacturer reserves the right to amend the content of subsequent editions without the obligation to inform its customers.